

## The Red Jacket Manifolded Submersible Turbine Pumping System

Increase Your Fueling Throughput with the 2+2 Horsepower (HP) Fixed Speed Solution

### **Increased Flow Rates**

The Red Jacket 2+2 HP Fixed Speed Solution Increases Flow Performance\*


- Maximize Throughput Capabilities Achieve 12 nozzles of flow at 10 Gallons Per Minute (GPM) / Nozzle
- Reduce Lines at Dispenser Supply fuel to 4 extra customers simultaneously while maintaining retail dispenser hydraulic specifications of flow at 10 GPM / Nozzle
- Fuel Customers Faster Customers will fuel more than 20% faster to fill 15 gallons with 16 nozzles running simultaneously





STP System

#### SIMULTANEOUS FLOW @ 10 GPM / NOZZLE



## REDUNDANCY = UPTIME

**Red Jacket Keeps Your Fuel Station Up & Running** 

#### **Automatic Failover**

- When paired with Red Jacket IQ Control Boxes, a 2+2 HP manifolded system turns on the secondary Submersible Turbine Pump (STP) if the primary STP becomes unable to pump fuel
- This allows the site to maintain fueling operations utilizing the secondary, manifolded STP
  - A fault code will be provided, allowing for troubleshooting and a service technician to be dispatched



veeder.com

### The Red Jacket Manifolded Submersible Turbine Pumping System


## PERFORMANCE OF LINE MANIFOLDED STPS


- IQ Control Boxes turn on the secondary STP only when needed
- Service one STP while the other keeps your site running

## POWER CONSUMPTION

# Red Jacket 2+2 HP Fixed Speed Solution Maximizes the Efficiency of Your Pumping System

- Less energy is used in low and high demand scenarios by only activating the secondary STP when required
- · Reduced power requirements with simple Control Box designs





## WHY RED JACKET FIXED SPEED STP TECHNOLOGY

The Red Jacket Manifolded STP System provides increased flow rates by adding a second STP. Serve your customers faster and gain peace of mind that the maximum flow rating of your dispensers is being met.

By using the Red Jacket manifolded pumping system, a single STP will only come on with the associated demand. Using a manifolded system, up to 35% energy savings can be realized per configuration\*. Running a larger HP motor will cause unnecessary energy to be used. It is simply more efficient to have a second motor come on with Demand Based Staging rather than to have a larger motor run for medium to large fueling applications. Supplemented with Red Jacket's industry proven reliability with less than 1% field failure rates, your STP system is built to last.

\* Compared to a 4 HP Variable Speed STP pumping system

125 Powder Forest Drive • PO Box 2003 • Simsbury, CT 06070 • ©2023 Veeder-Root • P/N 576047-476 Rev. A All information contained in this document is subject to change without notice.



+1.800.873.3313 | +1.814.695.4476 (International) | veeder.com