

Introduction

Purpose

This document provides instructions to read and display card data and calculate PINs for Gasboy Club Cards and Bank Cards, using the PIN Calculator.

Table of Contents

Торіс	Page
Introduction	1
Important Safety Information	3
Changing Modes	5
Reading a Card	5
Calculating the PIN	5
Power-up Error Messages	6

Related Documents

Document		
Number	Title	GOLD Library
MDE-4312	Site Controller II Configuration Manual v2.3	CFN Series Controllers and POS
MDE-4314	Site Controller III Configuration Manual for Windows v3.3	CFN Series Controllers and POS
MDE-4316	Site Controller III Configuration Manual for Windows NT® v3.4	CFN Series Controllers and POS

Abbreviations and Acronyms

Term	Description
PIN	Personal Identification Number
RAM	Random Access Memory
ROM	Read Only Memory

Warranty

For information on warranty, refer to MDE-4255 Gasboy's Warranty Policy Statement. If you have any warranty-related questions, contact Gasboy's Warranty Department at its Greensboro location.

Important Safety Information

This section introduces the hazards and safety precautions associated with installing, inspecting, maintaining or servicing this product. Before performing any task on this product, read this safety information and the applicable sections in this manual, where additional hazards and safety precautions for your task will be found. Fire, explosion, electrical shock or pressure release could occur and cause death or serious injury, if these safe service procedures are not followed.

Preliminary Precautions

You are working in a potentially dangerous environment of flammable fuels, vapors, and high voltage or pressures. Only trained or authorized individuals knowledgeable in the related procedures should install, inspect, maintain or service this equipment.

Emergency Total Electrical Shut-Off

The first and most important information you must know is how to stop all fuel flow to the pump/dispenser and island. Locate the switch or circuit breakers that shut off all power to all fueling equipment, dispensing devices, and Submerged Turbine Pumps (STPs).

\Lambda WARNING

The EMERGENCY STOP, ALL STOP, and PUMP STOP buttons at the cashier's station WILL NOT shut off electrical power to the pump/ dispenser. This means that even if you activate these stops, fuel may continue to flow uncontrolled.

You must use the TOTAL ELECTRICAL SHUT-OFF in the case of an emergency and not the console's ALL STOP and PUMP STOP or similar keys.

Total Electrical Shut-Off Before Access

Any procedure that requires access to electrical components or the electronics of the dispenser requires total electrical shut off of that unit. Understand the function and location of this switch or circuit breaker before inspecting, installing, maintaining, or servicing Gasboy equipment.

Evacuating, Barricading and Shutting Off

Any procedure that requires access to the pump/dispenser or STPs requires the following actions:



- An evacuation of all unauthorized persons and vehicles from the work area
- Use of safety tape, cones or barricades at the affected unit (s)
- A total electrical shut-off of the affected unit (s)

Read the Manual

Read, understand and follow this manual and any other labels or related materials supplied with this equipment. If you do not understand a procedure, call a Gasboy Authorized Service Contractor or call the Gasboy Service Center at 1-800-444-5529. It is imperative to your safety and the safety of others to understand the procedures before beginning work.

Follow the Regulations

Applicable information is available in National Fire Protection Association (NFPA) 30A; *Code for Motor Fuel Dispensing Facilities and Repair Garages*, NFPA 70; *National Electrical Code (NEC)*, Occupational Safety and Hazard Association (OSHA) regulations and federal, state, and local codes. All these regulations must be followed. Failure to install, inspect, maintain or service this equipment in accordance with these codes, regulations and standards may lead to legal citations with penalties or affect the safe use and operation of the equipment.


Replacement Parts

Use only genuine Gasboy replacement parts and retrofit kits on your pump/dispenser. Using parts other than genuine Gasboy replacement parts could create a safety hazard and violate local regulations.

Safety Symbols and Warning Words

This section provides important information about warning symbols and boxes.

Alert Symbol



Signal Words

These signal words used in this manual and on warning labels tell you the seriousness of particular safety hazards. The precautions below must be followed to prevent death, injury or damage to the equipment:



DANGER: Alerts you to a hazard or unsafe practice which will result in death or serious injury.

WARNING: Alerts you to a hazard or unsafe practice that could result in death or serious injury.

CAUTION with Alert symbol: Designates a hazard or unsafe practice which may result in minor injury.

CAUTION without Alert symbol: Designates a hazard or unsafe practice which may result in property or equipment damage.

Working With Fuels and Electrical Energy

Prevent Explosions and Fires

Fuels and their vapors will explode or burn, if ignited. Spilled or leaking fuels cause vapors. Even filling customer tanks will cause potentially dangerous vapors in the vicinity of the dispenser or island.

No Open Fire

Open flames from matches, lighters, welding torches or other sources can ignite fuels and their vapors.

No Sparks - No Smoking



Sparks from starting vehicles, starting or using power tools, burning cigarettes, cigars or pipes can also ignite fuels and their vapors. Static electricity, including an electrostatic charge on your body, can cause a spark sufficient to ignite fuel vapors. Every time you get out of a vehicle, touch the metal of your vehicle, to discharge any electrostatic charge before you approach the dispenser island.

Working Alone

It is highly recommended that someone who is capable of rendering first aid be present during servicing. Familiarize yourself with Cardiopulmonary Resuscitation (CPR) methods, if you work with or around high voltages. This information is available from the American Red Cross. Always advise the station personnel about where you will be working, and caution them not to activate power while you are working on the equipment. Use the OSHA Lockout/ Tagout procedures. If you are not familiar with this requirement, refer to this information in the service manual and OSHA documentation.

Working With Electricity Safely

Ensure that you use safe and established practices in working with electrical devices. Poorly wired devices may cause a fire, explosion or electrical shock. Ensure that grounding connections are properly made. Take care that sealing devices and compounds are in place. Ensure that you do not pinch wires when replacing covers. Follow OSHA Lockout/Tagout requirements. Station employees and service contractors need to understand and comply with this program completely to ensure safety while the equipment is down.

Hazardous Materials

Some materials present inside electronic enclosures may present a health hazard if not handled correctly. Ensure that you clean hands after handling equipment. Do not place any equipment in the mouth.

\Lambda WARNING

The pump/dispenser contains a chemical known to the State of California to cause cancer.

The pump/dispenser contains a chemical known to the State of California to cause birth defects or other reproductive harm.

In an Emergency

Inform Emergency Personnel

Compile the following information and inform emergency personnel:

- Location of accident (for example, address, front/back of building, and so on)
- Nature of accident (for example, possible heart attack, run over by car, burns, and so on)
- Age of victim (for example, baby, teenager, middle-age, elderly)
- Whether or not victim has received first aid (for example, stopped bleeding by pressure, and so on)
- Whether or not a victim has vomited (for example, if swallowed or inhaled something, and so on).



Gasoline ingested may cause unconsciousness and burns to internal organs. Do not induce vomiting. Keep airway open. Oxygen may be needed at scene.

WARNING




Gasoline inhaled may cause unconsciousness and burns to lips, mouth and lungs. Keep airway open.

Seek medical advice immediately.

Seek medical advice immediately.

WARNING



Seek medical advice immediately.

WARNING



Gasoline spilled on skin may cause burns. Wash area thoroughly with clear water. Seek medical advice immediately.

IMPORTANT: Oxygen may be needed at scene if gasoline has been ingested or inhaled. Seek medical advice immediately.

Lockout/Tagout

Lockout/Tagout covers servicing and maintenance of machines and equipment in which the unexpected energization or start-up of the machine(s) or equipment or release of stored energy could cause injury to employees or personnel. Lockout/Tagout applies to all mechanical, hydraulic, chemical or other energy, but does not cover electrical hazards. Subpart S of 29 CFR Part 1910 - Electrical Hazards, 29 CFR Part 1910.333 contains specific Lockout/ Tagout provision for electrical hazards.

Changing Modes

The PIN calculator reads cards in the READ mode and calculates PINs in the PIN mode. When it is in the READ mode, the display reads "READ". When it is in the PIN mode, the display reads "PIN". To change modes, press the push-button switch. The calculator alternates between the two modes when you press the push-button switch.

Reading a Card

To read a card, proceed as follows:

- 1 Ensure that the display reads "READ". If it does not, press the push-button switch.
- **2** Swipe a card through the reader slot in the direction of the arrows on the reader. The magnetic strip should face up. The calculator displays the first four digits on the card.
- **3** Press the push-button switch to display the next four digits on the card.
- **4** Hold down the push-button switch the calculator displays each four digits of card data for half a second. The calculator displays a hyphen (-) as the field separator.
- **5** After all the card data has been displayed, press the push-button switch to return the calculator to the READ mode.
- 6 If an error occurs when the card is read, the calculator will display "ERR". Press the pushbutton switch and swipe the card again.

Note: After waiting for 30 seconds, the calculator times out and blanks the display. Press the push-button twice to return the calculator to READ mode.

Calculating the PIN

To calculate the PIN for a card, proceed as follows:

- 1 Ensure that the display reads "PIN". If it does not, press the push-button switch.
- **2** Swipe a card through the reader slot in the direction of the arrows on the reader. The magnetic strip should face up. The calculator displays the PIN.
- **3** Press the push-button switch to return the calculator to the PIN mode.
- 4 If an error occurs when the card is read, the calculator will display "ERR". Press the pushbutton switch and swipe the card again.
- 5 If the card is not properly encoded, the calculator will display "BAD".

Note: After waiting for 30 seconds, the calculator times out and blanks the display. Press the push-button twice to return the calculator to READ mode.

Power-up Error Messages

When the calculator is powered up, it may display "RAM" or "ROM". If the calculator displays these messages, the unit is defective. Consult your Gasboy representative.

Windows NT® is a registered trademark of Microsoft Corporation.



© 2007 GASBOY 7300 West Friendly Avenue · Post Office Box 22087 Greensboro, North Carolina 27420 Phone 1-800-444-5529 · http://www.gasboy.com · Printed in the U.S.A. MDE-4706 Gasboy PIN Calculator Operation Instructions · November 2007