

MAX 1

HI-FLOW AUTOMATIC SHUT-OFF DIESEL NOZZLE



Automatic Confidence

The MAX 1 hi-flow diesel nozzle has the durability needed to perform in high-volume truck stop applications and service stations. Equipped with automatic shut-off features, this heavy-duty nozzle is specifically designed for unattended self-service and card-lock refueling locations.

Available as a standard or pressure-sensitive nozzle, the no-pressure/no-flow feature enables the station operator to control the dispensing of fuel while the customer has the convenience of a one-hand, hold-open mechanism for effortless dispensing.

12
MONTH

WARRANTY

-40F
DEGREE

SUPERIOR
COLD WEATHER
PERFORMANCE



MAX 1

HI-FLOW AUTOMATIC SHUT-OFF DIESEL NOZZLE

TECHNICAL DATA



Features & Benefits

- Certified UL/ULC 2586 listed
- Rugged, heavy-duty design
- All nozzles available as Self Serve (S)
- Unique attitude device (AD) provides automatic safety shut-off if spout is raised above horizontal or if the nozzle falls from the vehicle
- Pressure-sensitive design prevents spills in prepay fuel dispensing
- Dual poppet design makes the nozzle easier to open under high inlet pressure
- Longer spout with Anchor Bushing (AR) available upon request for improved durability
- Cover and handguard material designed to protect customers' vehicles
- Mates with all standard hardwall or softwall 1" hoses
- NPT and BSPP threads available
- Custom logo available upon request
- All major oil company colors available

MODELS

- NM1P-AR-AD** | AUTOMATIC DIESEL NOZZLE | *With 2-step Hold-open Device, Attitude Device, Anchor Bushing, Full Scuff Guard and Splash Shield*
- NM1P-0-03-0** | AUTOMATIC DIESEL NOZZLE | *No Hold-open device with Trickle Flo Poppet, Attitude Device, Anchor Bushing and Full Scuff Guard*
- NM1P-0-01-3** | AUTOMATIC DIESEL NOZZLE | *With 3-step Hold-open Device, Trickle Flo Poppet, Attitude Device and Full Scuff Guard*
- NM1P-0-02-3** | AUTOMATIC DIESEL NOZZLE | *With 3-step Hold-open Device, Trickle Flo Poppet, Anchor Bushing and Full Scuff Guard*

ACCESSORIES

Breakaways 	CTM100 1" CAM TWIST Magnetic Breakaway CTM100-L 1" CAM TWIST Lower-Half Breakaway C100N 1" Single-Use Breakaway	Scuff Guards Available Pantone® Colors:	 <table border="0"> <tr> <td>■ RED- 200 C</td> <td>■ BLUE- 286 C</td> </tr> <tr> <td>■ BLACK- BLACK C</td> <td>■ YELLOW- 128 C</td> </tr> <tr> <td>■ GREEN- 348 C</td> <td>■ ORANGE- 144 C</td> </tr> </table>	■ RED- 200 C	■ BLUE- 286 C	■ BLACK- BLACK C	■ YELLOW- 128 C	■ GREEN- 348 C	■ ORANGE- 144 C
■ RED- 200 C	■ BLUE- 286 C								
■ BLACK- BLACK C	■ YELLOW- 128 C								
■ GREEN- 348 C	■ ORANGE- 144 C								
Swivels 	C720 1 x 1 1" M x 1" F Twister Swivel	Splash Shields Available Pantone® Colors:							
Swivel/Breakaways 	ISBA-100N IN-LINE SWIVEL/BREAKAWAY Compatible with 3/4" nozzles and hoses and all fuel blends up to E85 and B20								
Spout Assemblies 	Available through Catlow Customer Service								