

VAPT7.E37780 - Solenoids for Use in Hazardous Locations Certified for Canada

Solenoids for Use in Hazardous Locations Certified for Canada

[See General Information for Solenoids for Use in Hazardous Locations Certified for Canada](#)

PETER PAUL ELECTRONICS CO INC

E37780

480 John Downey Dr
PO BOX 1180
New Britain, CT 06051-2910 USA

Class I, Groups C and D; Class I, Div. 2, Groups A, B, C and D; Class II, Groups E, F and G.

Model Nos. OE21-26 incl., OEH22 followed by Z, followed by additional suffix letters or letters with a number, followed by a single letter, followed by BC, BCC, C, CC E or EC, followed by F, H, M or P. Solenoids with suffix P or F may be marked "Rain tight".

Model Nos. OE21-26 incl., OEH22 followed by additional suffix letters or letters with a number, followed by D, U, X, Z, followed by B, C, CC E or EC, followed by A, F, H, M, P or S, followed by additional numbers. Solenoids with suffix P or F may be marked "Rain tight".

Models OE51, 52, 53, 54, 55, or 56, may be preceded by V or V0, followed by Z, followed by any four digit number, followed by any single letter, followed by C, CC, E, or EC, followed by H, M, P, or F.

Models OEL51, 52, or 53, may be preceded by V or V0, followed by Z, followed by any four digit number, followed by any single letter, followed by S, C, CC, H, M, P, F, E, or EC. Solenoids with suffix P may be marked "Rain tight".

Models OELL51, 52, or 53, may be preceded by V or V0, followed by Z, followed by any four digit number, followed by any single letter, followed by S, C, CC, H, M, P, F, E, or EC. Solenoids with suffix P may be marked "Rain tight".

Models OE51, 52, 53, 54, 55, or 56, may be preceded by V or V0, followed by a single suffix, followed by a single suffix, followed by D, followed by D, U, Z, X, or W, followed by B, C, CC, E, or EC, followed by M, P, A, S, D, H, or F, followed by 6, 9, 12, 24, 28, 48, 60, 72, 76, 100, 110, 115, 120, 125, 127, 139, 141, 143, 200, 208, 215, 220, 230, 240, 245, 253, 380, 415, 440, 460, or 480, followed by 50 or 60.

Models OEL51, 52, or 53, may be preceded by V or V0, followed by a single suffix, followed by a single suffix, followed by D, followed by D, U, Z, X, or V, followed by B, C, CC, E, or EC, followed by M, P, A, S, H, or F, followed by 5, 6, 12, 24, 48, 110, 120, 230, or 240, followed by 50 or 60. Solenoids with suffix P may be marked "Rain tight".

Models OELL52, or 53, may be preceded by V or V0, followed by a single suffix, followed by a single suffix, followed by D, followed by D, U, Z, X, or V, followed by B, C, CC, E, or EC, followed by M, P, H, or F. Solenoids with suffix P may be marked "Rain tight".

Models OEL21, OEL22, OEL23, OEL24, OEL25 or OEL26, followed by any single letter A through Z, followed by any single letter A through Z, followed by D, followed by D, U, Z, or X, may be followed by B, followed by C, CC, E, or EC, followed by P or F, followed by 12 or 24. May be prefixed by V or VO.

Models OEL21, OEL22, OEL23, OEL24, OEL25 or OEL26, followed by Z, followed by any four numbers, followed by any single letter A through Z, may be followed by B, followed by C, CC, E, or EC, followed by P or F, may be followed by additional letters A through Z. May be prefixed by V or VO.

Last Updated on 2020-04-08

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission

from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2021 UL LLC"