

# SINGLE-USE IN-LINE BREAKAWAYS

ELIMINATE SPILLS CAUSED BY DRIVE-OFFS



## Heavy-Duty Guardian

The Catlow C86NT (3/4") and C100N (1") Single-Use Breakaways are industry leaders. Small and lightweight, these minimal flow restriction breakaways are designed to be installed between the whip hose and the primary hose. The internal dual poppets close when a drive-off occurs, trapping the fuel inside the hoses at both ends to prevent costly fuel spills and possible damage to the environment.

The C100N is a rugged, heavy-duty in-line breakaway designed for truck stops and high-volume stations that allow for high capacity fueling with little pressure drop.



**350**  
POUNDS

MAXIMUM  
SEPARATION  
FORCE

**12**  
MONTH

WARRANTY



# SINGLE-USE IN-LINE BREAKAWAYS

ELIMINATE SPILLS CAUSED BY DRIVE-OFFS

## TECHNICAL DATA



## Features & Benefits

- UL/ULC listed for Diesel, Gasoline and ethanol blends up to 10%
- Meets NFPA 30A Codes
- Maximum separation force is designed at 350 lbs.
- C86NT mates with all 3/4" and 5/8" hoses
- C100N mates with all 1" hoses
- Durable protective cover minimizes damage to vehicles and the breakaway during a drive-off
- Seals both ends of the breakaway after separation
- 12 month warranty

## SINGLE-USE MODELS

**C86NT** | 3/4" SINGLE-USE IN-LINE BREAKAWAY

**C100N** | 1" SINGLE-USE IN-LINE BREAKAWAY

## C100N FLOW RATE ANALYSIS

