

## Extend the Life of Your Hoses

Catlow's 360-degree in-line swivel eliminates kinking and twisting of the hose, making it easier for customers to manipulate the nozzle while also extending hose life. The high-tech engineering and design offer a smoother flow for higher volume systems. The ILS can be installed at either the nozzle or dispenser, and it does not affect existing hose length. It mates with all standard, diesel, and high-flow bulk fueling hoses with NPT threads and 3/4" British.



**1M**  
CYCLES

EXCEPTIONAL  
DURABILITY

**-40F**  
DEGREE

SUPERIOR  
COLD WEATHER  
PERFORMANCE

**UL**

UL LISTED

**12**  
MONTH


WARRANTY

# ILS

## IN-LINE SWIVELS

### TECHNICAL DATA

**ENCAPSULATED NYLON SWIVEL BEARING**  
Self Lubricating for Long Service Life



**2 - O-RING SEALS**  
Accomodate a Wide Range of Fluids, Fuels & Temperatures



### Features & Benefits

- UL Listed for Gas, E25, E85, Diesel, and B20
- 360-degree nozzle rotation for easy handling and hose control
- Minimal restriction on fuel flow
- Climate ready for extreme temperatures -40°F to 125°F (-40°C to 52°C)
- Does not affect existing hose length
- Mates with all standard, diesel, and high-flow bulk fueling hoses with NPT and British Parallel threads
- Tested to more than 1,000,000 cycles\*

### STANDARD FUELS ILS MODELS

**ILS-N7575** | 3/4" NPT to 3/4" NPT

**ILS-N100100** | 1" NPT to 1" NPT

### ETHANOL BLENDS TO E85 ILS MODELS

**ILS-N7575F** | 3/4" M X 3/4" F | **E85**

**ILS-M75F** | M34 x 3/4" NPT | **E85**

**ILS-M75** | 3/4" NPT to 3/4" NPT | **E85**

\* BASED ON INTERNAL CATLOW TESTING